

section II NORMAL PROCEDURES

CDC-1-32

STATUS OF AIRCRAFT.

FLIGHT RESTRICTIONS.

Refer to Section V for limitations on the aircraft.

CRUISE CONTROL.

Refer to Appendix I to determine fuel, airspeeds and power settings required for safe and efficient completion of the proposed mission.

WEIGHT AND BALANCE.

Know the take-off and anticipated landing gross weight and balance. Refer to weight limitations specified in Section V; Handbook of Weight and Balance, T. O. 1-1B-40; and Basic Weight Check List, T. O. 1C-45G-5. Refer also to Form F to ascertain loading is within weight and balance limits.

BEFORE EXTERIOR INSPECTION.

Personal gear should be stowed aboard and the following safety check completed:

Ignition Switches - OFF.

Battery Switches - OFF.

Landing Gear Lever - DOWN.

Flight Controls - Unlocked.

Check engineering status on USAF Form I.

EXTERIOR INSPECTION.

The exterior check will begin at the cabin door and proceed clockwise around the aircraft (figure 2-1) ending at the cabin door. The following inspection will be accomplished:

- 1.—Fuselage — Skin and windows for damage.
Top antennas — Taut and securely mounted.
- 2.—Left fuel access doors — Closed and secured.

Left wing, top surface — No skin damage or leakage from the nacelle.

Left flap — Top and bottom surfaces undamaged and hinges secure.

- 3.—Left Aileron — Top and bottom surfaces undamaged, no play in hinges and unobstructed full travel. Bonding intact.

Aileron trim tab — Securely hinged and in a neutral setting.

- 4.—Left wing tip — Undamaged with the left position light securely installed.

- 5.—Deicer boot — Securely attached and undamaged.

Passing light — Unbroken and securely in place.

Left wing, bottom surface — Skin surface undamaged and free of any accumulation of mud or dirt. Landing light fully retracted, clean and unbroken, wing tie-down removed.

- 6.—Left engine cowl — Securely fastened.

Left cowl flaps — Mechanical linkage secure.

External power — Connected.


CAUTION

External power should be used for starting the aircraft to relieve the batteries of the extra load. Starting by use of the aircraft batteries is emergency procedure.

Left landing gear doors — Linkage and hinge secure; and the structure undamaged.

Left landing gear shock strut — 2½ inches of extension.

EXTERIOR INSPECTION



CDC-1-33

Figure 2-1

CAUTION

Damage to the landing gear may result if the aircraft is operated when there is less than $1\frac{1}{2}$ inches of shock strut extension after the aircraft is loaded. Below this minimum, shock absorbing action is insufficient for landing.

- Left brake actuators — No leakage.
- Left tire — Properly inflated and without cuts, cracks or badly worn areas.
- Wheel chocks — In place.
- Left propeller blades and hubs — No cracks, nicks or deep scratches. No apparent leakage.
- Left engine — No crankcase leakage. Air scoops unobstructed.
- Landing gear wheel well — No apparent engine or hydraulic oil leakage. No ruptured tubing, broken wiring or damaged equipment. Entire compartment free of any accumulation of oil. Landing gear slide tube free of dust or dirt.

WARNING

The area surrounding the aircraft will be inspected for evidence of leakage or spillage of inflammable liquids which might be ignited during the starting operation.

- 7.—Aircraft belly — Antennas taut and forward mounts secure. All access doors secure. Belly skin and structure undamaged.
- 8.—Pitot tubes — Uncovered and unobstructed.
Nose compartment — Door closed and securely latched.
Taxi lights — Lens clean and unbroken. Retaining rings secure.
- 9. through 13.—The right engine, engine cowl, propeller, landing gear, tire, wing, deicer, aileron, flap, lights and fuel access doors will be inspected in the manner prescribed for the corresponding left-hand components.
- 14.—Fuselage — Skin and windows for damage.
- 15.—Aft belly antenna mount — Secure.
Right static port — Unobstructed.

Horizontal stabilizer — Top and bottom surfaces of the left side undamaged. Deicer boot undamaged and secure.

- 16.—Right vertical stabilizer — Securely attached and undamaged.

Right rudder — Undamaged, bonding intact, no hinge play and unobstructed through its full range of travel.

- 17.—Elevator — Top and bottom surfaces undamaged. Unobstructed through the full range of travel. Hinges secure with no apparent play. Bonding intact.

Top of aircraft fuselage — Undamaged.

Tail position light — Securely attached and undamaged.

Elevator tab — Undamaged with hinges and linkage secure. Note position.

Tail cone drain — Unobstructed.

- 18.—Left rudder — Unobstructed through the full range of travel, undamaged, securely hinged, no hinge play and bonding intact.

Rudder trim tab — Set in neutral and undamaged. Hinges and linkage secure.

Vertical stabilizer — Undamaged and securely mounted.

Horizontal stabilizer — Top and bottom surfaces of the left-hand side undamaged. Deicer boot undamaged and secure.

- 19.—Tail wheel assembly — Structure undamaged and free of an accumulation of mud, rust or dirt which would restrict operation.

Left static port — Unobstructed.

Aft belly antenna mount — Secure.

Fuselage — Portion aft of the cabin door undamaged.

Tail tie-down — Removed.

ON ENTERING AIRCRAFT.

CABIN COMPARTMENT.

After entering the aircraft, the main cabin door should be checked, noting the security of the latch.

The lavatory compartment should be inspected. Weight and balance limitations do not permit stowage of gear in this compartment. First aid kits in place.

Proceeding forward through cabin, check as follows:

There should be no loose gear in the cabin area.

There are to be seat belts available to all passengers.

Emergency escape hatch — Secure.

Fire extinguisher — In place and secure.

BEFORE ENTERING PILOT COMPARTMENT.

Generators — Check ON.

Anti-icer tank gage — Full.

PILOT COMPARTMENT.

Loose gear — Stowed or removed.

Control lock — Stowed.

Seat, safety belt and shoulder harness — Adjusted.

All control tab indicators — Coincide with the actual positions.

(Battery switches — ON for this check, then — OFF.)

All ignition switches — OFF.

Engine selector — OFF.

Ignition booster, starter and primer switches — Cover down.

Battery switches — OFF. (Do not use ship's batteries for starting except in emergencies.)

Fuel booster switches — OFF.

Instrument inverter switch — OFF.

All light switches — OFF.

Fuel quantity gage — Check all tanks.

Propeller levers — TAKE-OFF RPM.

Manifold heat levers — COLD.

Throttles — CLOSED.

Mixture levers — IDLE CUT OFF.

Oil shutter levers — COLD.

Cowl flap handles — OPEN.

Landing gear lever — DOWN.

Flap lever — UP (Flaps retracted).

NOTE

If flaps are not fully retracted, retract them to prevent damage from objects which may be thrown against their lower surface.

Left engine fuel selector handle — OFF.

Tail wheel handle — LOCKED.

Right engine fuel selector handle — OFF.

Parking brake handle — ON.

Oil by-pass button — COLD.

Landing gear circuit breaker — Check. (Push to reset.)

Engine fire extinguisher switches — Check safetied.

NOTE

If the safety wire is broken on the guards for the extinguisher switches, it may be the system has been discharged. The pressure gage should be checked.

Fuel cross-feed handle — OFF.

Propeller anti-icer — Place knob at NORMAL.

Allow to remain a few seconds and check for alcohol flow at the propeller. Return knob to OFF.

NOTE

If there is no indication of alcohol flow within a few seconds with the knob at NORMAL, the knob should be slowly turned toward MAX and the position at which flow begins noted.

Deicer button — OFF.

Pitot heat switches — OFF.

Windshield wiper switch — OFF.

All indicator lights — Push to test.

Pilot's instruments lights knob — OFF.

Engine and subpanel instruments lights knob — OFF.

Pilot's turn-and-bank power selector switch — NORMAL.

Propeller feathering circuit breaker — Check ON.

Manifold pressure gage — Check (Note indication for power check).

NOTE

Manifold pressure gages should indicate the current barometric pressure. Any variation should be noted.

Copilot's instruments lights knob — OFF.

ADDITIONAL CHECK (NIGHT FLIGHT).

If operation during the hours of darkness is initiated or anticipated, the following additional checks will be completed:

All interior and exterior lights — Check for proper operation.

Flashlight — In operating condition and accessible to the pilot.

STARTING ENGINES.

As a precaution against liquid lock, each engine should be pulled through 4 blades. This may be accomplished with the starter when external power is utilized. The starter should be used intermittently in such a manner that rotation will be in approximately 90-degree increments.

NOTE

A liquid lock will be recognized by the resistance it offers to rotation. When liquid lock is detected, it is not to be relieved by turning the engine in either direction. The spark plugs for those cylinders affected are to be removed and all fluid drained.

Determine that the area to the rear of the aircraft is clear and that no damage will result from the propeller air stream.

The fire guard, who is to stand by for all starts, should be in such position that he is visible to the pilot to indicate the area is "clear." No start should be attempted until the "clear" signal is received. The left engine should not be started with the cabin door open.

RIGHT ENGINE.

Right Engine Fuel Selector Handle — RIGHT FRONT.

Right Cowl Flap Handle — Check OPEN.

Right Throttle — $\frac{1}{8}$ OPEN.

Right Mixture Lever — FULL RICH.

Right Fuel Booster Switch — ON.

Master Ignition Switch — ON.

Engine Selector Switch — RIGHT.

Starter Switch — ON.

— Allow engine to turn two revolutions, then:

Right Ignition Switch — BOTH.

Ignition Booster Switch — ON.

Primer Switch — Use until the engine fires and is operating smoothly.

Starter Switch — Release.

Ignition Booster Switch — Release.

NOTE

If engine ceases to fire after starting, move the Mixture Lever to IDLE CUT OFF until it again begins to fire. Then return the Mixture Lever to FULL RICH.


CAUTION

Overheating of the starter motor will occur with prolonged operation. Thirty seconds should be considered as the maximum period of continuous operation without a cooling period.

Adjust engine speed to 1000 rpm.

Fuel Booster Switch — OFF.

Engine Selector Switch — OFF.



CDC-1-34

CAUTION

If oil pressure is not indicated within 30 seconds after starting, shut down engine and investigate.

Refer to Section III for the procedure to be followed in the event of engine fire.

Position controls and start the left engine in the manner prescribed for the right engine.

Instrument Inverter — ON.

All components of the radio system should be individually checked for proper operation.

Receivers should be checked in each tuning range, if multiple and on a known frequency for proper calibration.

Direction finding equipment is to be operated both manually and automatically and checked visually and aurally. The visual indicator should be checked on a known station for proper indication.

Each transmitter should be checked on more than one frequency to determine proper operation of the remote tuners.

NOTE

Since the marker beacon receiver cannot usually be adequately checked on the ground, it should be both visually and aurally noted at the first opportunity in flight. During the radio check, local altimeter setting and correct time should be obtained and the instruments correctly set.

CAUTION

Since the generators are not operative at warm-up rpm, the radio check is to be accomplished on external power. If engines are warm and there is a possibility of overheating, this check may be made prior to starting.

External Power — Disconnect.
Battery Switches — ON.

ENGINE GROUND OPERATION.

When oil pressure has stabilized within limits, engine speed should be increased to the smoothest operating speed between 1200 rpm and 1600 rpm for the remainder of the warm-up period.

Avoid prolonged ground operation because of the high cylinder head temperatures that may result.

NOTE

For any given throttle setting, maximum cooling will result from maximum rpm. Therefore, for all ground operation the propeller control lever should be positioned for TAKE-OFF RPM.

GROUND TESTS.

For the ground testing of systems and accessories the

aircraft should be headed into the wind, the tail wheel locked and the parking brake set. Checks of the generator, flap and propeller systems are combined.

1. Engine Speed — 1600 rpm.
2. Right propeller feathering button — PUSH until drop of approximately 200 rpm then pull out.

NOTE


If the engine is operating at approximately 1500 rpm before feathering, it will continue to run fully feathered at about 450 rpm. Under these conditions, once the propeller is feathered, it will tend to slowly and steadily come out of the feathered position. This should not be considered abnormal since it is caused by the engine oil remaining under pressure.

3. Right propeller — UNFEATHER (Pull feathering button).

NOTE

(Deleted)

4. Repeat for the left propeller.
5. Left battery and generator switches — OFF.
6. Voltmeter selector switch — RIGHT.
7. Retard throttle to 900 rpm.
8. As engine speed decreases, the generator control circuit should disconnect the generator. This should occur at approximately 1000 rpm and will be indicated by a sudden "drop-off" of the volt and loadmeters.
9. Advance throttle on the right engine to 1900 rpm.
10. Observe volt and loadmeters — generators should reconnect at approximately 1200 rpm.
11. Lower flaps approximately 25 degrees. While the flaps are operating, observe the load and volt-




meter readings. The flap motor should draw approximately .3 load and the voltage should not exceed 29 volts.

12. Check if flaps are in the indicated position.
13. Pull the right propeller lever back to the LOW RPM (high pitch) position. Engine speed should stabilize at approximately 1200 rpm.
14. Return the right propeller lever to TAKE-OFF RPM position. Engine should again stabilize at 1900 rpm.
15. Lower flaps full down. Operation of the flap limit switches can be checked by noting the generator load drop-off as the flaps reach the FULL DOWN position.
16. Retard the right engine to warm-up rpm.
17. Left battery and generator switches — ON.
18. Right battery and generator switches — OFF.
19. Voltmeter selector switch — LEFT.
20. The left propeller and generator systems are checked in the same manner as the right (steps 7 through 17), with the exception that flaps are raised instead of being lowered.
21. Voltmeter selector switch — LEFT.
22. If icing is anticipated, check boots for proper operation by pulling the deicer button out and watching the boots go through several complete cycles.
23. Set and uncage gyros.
24. Instrument vacuum — Check.
25. Pitot heat — Check. (Increase on the load-meter indicates operation.) Each engine, having been operated on their respective main tanks, should now be checked on other tanks in the following manner:
26. Fuel cross-feed — On.
Right engine fuel selector handle — NOSE.
Left engine fuel selector handle — OFF. Leave in this position 15 seconds.
27. Left engine fuel selector handle — NOSE.
Right engine fuel selector handle — OFF.
Leave in this position 15 seconds.
28. Left engine fuel selector handle — LEFT REAR.
Right engine fuel selector handle — RIGHT REAR.
Fuel cross-feed handle — OFF. Leave in this position 15 seconds.
29. Left engine fuel selector handle — LEFT FRONT.
Right engine fuel selector handle — RIGHT FRONT.

TAXIING INSTRUCTIONS.

Have chocks pulled and release the parking brake. As the aircraft first begins to move, brakes should be applied to determine that adequate brake is available for stopping. It can also be noted if there is grab, drag or other malfunction of either brake.



CSC-135

The tail wheel must be unlocked before attempting any turn.

In taxiing, pilot visibility is restricted by the nose, in an area to the right and forward of the aircraft. To determine adequate clearance in this area will require an occasional S-turn.

Insofar as is possible, directional control should be maintained and turns executed by varying the power of the engines. This will permit minimum use of brakes.

The tendency for this aircraft to nose-over is not critical; however, brake application should be made with caution when the aircraft is empty or lightly loaded.

During taxiing turns, the gyro instruments should be checked for proper operation.

BEFORE TAKE-OFF.

PREFLIGHT ENGINE CHECK.

1. Both engines idle speed — Check (500 rpm).
2. Advance both engines to 700 rpm.
3. Ignition Switch — Check.
Turn right ignition switch to OFF. As soon as it is determined that the engine ceases to fire, return the switch to BOTH. Repeat for the left engine. Any delay in returning the switch to BOTH after the engine has stopped may result in backfire.
4. Advance both throttles to Field Barometric pressure.
5. Check RPM. The engine speed should be approximately 1950 ± 50 rpm.
6. Left Engine — Warm-up rpm.
7. Right Engine Ignition — Check.
Advance the throttle to field barometric pressure. Switch from BOTH to R, observe rpm, return to BOTH and allow rpm to stabilize. Switch from BOTH to L, observe rpm, return to BOTH. The maximum allowable drop is 65 rpm in either the R or L switch position.

CAUTION

To avoid detonation, a period of 1 minute will be considered maximum for operating the engine on single ignition at this speed.

8. Right Engine — 1700 rpm.
9. Cruising Fuel Air Mixture — Check.
Move mixture control into the MANUAL LEANING RANGE until an approximate 100 rpm drop is noted; then return to RICH. During this operation the engine speed should increase very slightly before decreasing. An immediate decrease indicates the mixture is set too lean; a momentary increase in excess of 25 rpm indicates the mixture is set too rich.
10. Right Engine Oil Temperature — Check.
11. Right Engine Oil Pressure — Check.
12. Right Fuel Pressure — Check.
13. Right Cylinder Head Temperature — Check.
14. Right Manifold Heat — HOT and check for carburetor mixture temperature rise.
15. Right Manifold Heat — COLD.
16. Right Engine — Warm-up rpm.
17. Left Engine — 1950 rpm.
18. Check left engine in the same manner as steps 7 through 16 for the right engine.

NOTE

Throughout the engine check, with the mixture RICH, acceleration or deceleration should be both smooth and rapid with no tendency to miss or backfire.

19. Battery Switches — ON.
20. Fuel Booster Switches — ON.
21. Propeller Levers — TAKE-OFF RPM.
22. Manifold Heat Levers — COLD.
23. Mixture Levers — RICH.
24. Oil Shutter Levers — As required.
25. Pedestal Levers Friction Locks — Tighten to prevent creeping.
26. Right Engine Fuel Selector — RIGHT FRONT.
27. Left Engine Fuel Selector — LEFT FRONT.

PREFLIGHT AIRCRAFT CHECK.

- Elevator Tab Wheel — Set for take-off.
- Rudder Tab Crank — NEUTRAL.
- Aileron Tab Wheel — NEUTRAL.
- Flaps — Retracted.
- Deicer Button — OFF.
- Pitot Heat Switches — As required.
- Gyro Instruments — Set and uncaged.
- Instrument Inverter Switch — ON.
- Safety Belt and Shoulder Harness — Check.
(Shoulder harness unlocked.)
- Flight Controls — Check for free and correct movement.

WARNING

If atmospheric conditions are conducive to the formation of carburetor ice, the induction system should be cleared, immediately before take-off, with manifold heat. Take-off, however, is to be made with the manifold heat levers in the COLD position to obtain maximum power. Heat may be re-applied when maximum power is no longer required.

TAKE-OFF.

The following techniques, when employed, will produce the results set forth in the Take-Off Curve, Appendix I.

WARNING

Do not take-off or land with the lavatory compartment occupied. The occupying of this compartment exceeds weight and balance limitations.

NOTE

Cylinder head temperature will increase 25° C to 50° C (45° F to 90° F) during the take-off run. Prior to take-off, temperatures should be sufficiently low that this increase will not cause the maximum allowable temperatures to be exceeded.

Tail Wheel Handle — LOCKED.

Cowl Flap Handles — TRAILED.

Apply take-off power with a slow, easy throttle movement.

NORMAL TAKE-OFF.

Take-off power is to be used for all take-offs. It is to be maintained until all obstacles have been cleared and the "Best Rate-of-Climb" speed is reached.

Directional control by use of the rudder is ineffective at airspeeds of less than 35 mph (30 knots) IAS. No attempt to raise the tail on take-off run below these minimums should be made.

There will be a tendency for the aircraft to "lift off" at 85 to 90 mph (74 to 78 knots) IAS and very little control pressure will be necessary at this speed to become airborne. This characteristic makes it possible for the aircraft to be "flown off" the ground, as compared to the more definite and abrupt "pull-off".

CROSS-WIND TAKE-OFF.

The only particular problem encountered making cross-wind take-offs with this aircraft is directional control at slow speeds. During the take-off runs, control can be facilitated by the application of power with the up-wind engine slightly in advance and in excess of power supplied by the down-wind engine, holding the tail down a little longer than for a normal take-off to minimize the weather-vaning tendency and by use of up-wind aileron. When enough speed

for directional control by rudder has been attained, the power output of the engines should be equalized. At approximately 60 mph the tail should be lifted and the aircraft flown off as soon as practicable.

NIGHT TAKE-OFF.

Normal take-off technique can be employed for night take-offs with the exception that acceleration after take-off should be accomplished in a climbing attitude. No level-off to attain "Best Rate-of-Climb" speed should be made under the reduced visibility conditions encountered at night.

MINIMUM RUN TAKE-OFF.

The following procedure for take-off is to attain a minimum take-off run.

Flaps — 15-degrees down.

Take position on the runway.

While holding the toe brakes, apply take-off power. Release brakes.

Raise the tail in a normal manner.

NOTE

Hold control column in full aft position until brakes are released and aircraft begins to roll.

At an IAS of approximately 70 mph (60 knots), apply elevator pressure to pull the aircraft off the ground.

When the aircraft is airborne, level off to accelerate.

Landing gear — UP.

Flaps — UP.

TAKE-OFF TO CLIMB OVER OBSTRUCTIONS.

For maximum performance when take-off with a climb-out over obstructions is required, the procedure for "minimum take-off run" is employed up to the stage where the aircraft becomes airborne. From that point it varies as follows:

When airborne, Landing Gear — UP.

Maintain a climbing attitude, but allow acceleration to 100 mph (86 knots) IAS as rapidly as possible.

Maintain this airspeed in climb until all obstructions are cleared.

Level off to accelerate, retracting flap when maximum flap speed is reached.

Re-establish a climbing attitude after attaining "Best Rate-of-Climb" speed.

AFTER TAKE-OFF.

Immediately after take-off, climb to a safe altitude, level off and maintain level flight until "Best Rate-of-Climb" speed is attained. Retract landing gear. (Gear retraction required 4 seconds.) Retract as soon as practicable since single-engine performance is greatly improved with the gear in the UP position.

WARNING

Before raising the landing gear, be certain that the aircraft is not only airborne but

sufficient control can be exercised to maintain flight. Any settling back to the runway with the landing gear unlocked and in an intermediate position will result in structural damage or complete collapse of the landing gear assembly.

CAUTION

Except under conditions of emergency and to prevent damage to the retracting mechanism, landing gear operation should never be reversed. That is, the lever should not be placed in the DOWN position while the gear is retracting or in the UP position while the gear is extending.

WARNING

At no time should the landing gear be retracted when sufficient runway for landing, in an emergency, remains ahead of the aircraft.

When the aircraft has reached its cruising altitude, trim for level flight and maintain climb power until cruising airspeed is attained. Accomplish the following:

Establish cruise power.

Fuel Booster Switches — OFF.

Mixture Levers — Adjust.

Manifold Heat Levers — As required.

Oil Shutter Levers — As required.

Right and Left Engine Fuel Selector Handles — REAR Tanks.

Cowl Flap Handles — CLOSED.

CLIMB.

See Take-off, Climb and Landing Curves in Appendix I. For climb performance, as specified in Appendix I, set up power for climb and establish an attitude which will produce the best rate-of-climb for your particular altitude.

FLIGHT CHARACTERISTICS.

Refer to Section VI for information regarding flight characteristics.

SYSTEMS OF OPERATION.

For information regarding the operation of the various systems, refer to Section VII.

DESCENT.

Preparatory to starting normal descent, accomplish the following:

Left Engine Fuel Selector Handle — LEFT FRONT.

Right Engine Fuel Selector Handle — RIGHT FRONT.

Fuel Cross-Feed Handle — OFF.

Mixture Lever — RICH.

NOTE

The Mixture Lever should be positioned in **RICH** for all descents since the correct mixture at cruising altitude will be excessively lean as more dense atmosphere is encountered at lower altitudes.

Manifold Heat Lever — As required.

Reduce power to establish the desired rate of descent and trim the aircraft. Maintain constant airspeed throughout. Use power variations to increase or decrease the rate of descent as desired. Frequently note that cylinder head temperatures are within operating limits.

CAUTION

In determining the necessity of manifold heat, it should be remembered the fuel air ratios and power settings normally used during descent offer those conditions which are most conducive to the formation of ice in the induction system.

PRE-TRAFFIC PATTERN CHECK.

The purpose of the Pre-Traffic Pattern Check is to prepare the aircraft for landing, insofar as is practicable, well in advance of the period when the pilot's full attention is required in observing other traffic and landing. In this check, proceed as follows:

- Altimeters — Set (Local altimeter setting).
- Gyros — Set and uncaged.
- Fuel Booster Switches — ON.
- Fuel Quantity — Check.
- Mixture Lever — **FULL RICH**.
- Left Engine Fuel Selector Handle — **LEFT FRONT**.
- Tail Wheel Handle — **LOCKED**.
- Right Engine Fuel Selector Handle — **RIGHT FRONT**.
- Brakes — Check.
- Parking Brake Handle — **OFF**.
- Fuel Cross-Feed Handle — **OFF**.
- Landing Weight — Check.
- Seat belts and shoulder harness, crew and passengers — Secure.

Enter the traffic pattern at 120 mph (105 knots) IAS at an altitude of 1000 feet.

TRAFFIC PATTERN CHECK LIST.

- Propeller Levers — Set for 2000 rpm.
- Manifold Heat Levers — As required.
- Oil Shutter Levers — As required.
- Deicer Button — **OFF**.
- Landing Gear Lever — **DOWN**.
- Recheck landing gear for down and locked position by use of all indicators and by visual check.

NOTE

(Deleted)

Decrease IAS to 115 mph (100 knots).

Cowl Flap Handles — As required.

Flap Lever — **DOWN**.

Immediately prior to flare out:

Propeller Levers — **TAKE-OFF RPM**.

NOTE


If it is necessary to use manifold heat during the approach to landing, the manifold heat levers should be placed **COLD** prior to landing. This should be accomplished at the time propeller levers are positioned for **TAKE-OFF RPM**. Manifold heat levers are managed in this fashion so that full power will be available for go-around if the landing cannot be completed.

LANDING.**NORMAL LANDING.**

There are no outstanding characteristics peculiar to this particular aircraft in landing. The effectiveness of control remains positive throughout the range of decreasing speed and in none of the various operations are control pressures excessive. The procedure outlined in this section will produce the results shown on the landing chart in Appendix I. As with all aircraft, a number of checks and operations must be accomplished in a relatively short period of time. Unless routine checks are accomplished prior to beginning the actual approach to landing, your technique will suffer. On a downwind leg, all checks should be completed, the landing gear extended and speed reduced to 115 mph (100 knots) IAS.

Flaps may be used, on the approach, at the discretion of the pilot. On final approach, speed should have been reduced to 105 mph to 92 mph (90 knots to 80 knots) IAS and full flap applied. Over the end of the runway close the throttle and complete the portion of the check list that is required before flare-out. Through the steady application of back pressure, flare-out the glide angle and establish a slight tail low attitude.

Throughout the approach, trim the aircraft to relieve elevator pressure as more control is applied to reduce airspeed. Maintain the desired rate-of-descent with power variation rather than causing airspeed fluctuation by using elevators. When the aircraft main wheels have settled firmly on the ground, apply sufficient forward pressure to keep the aircraft in a level attitude and firmly on the runway. At approximately 60 mph the tail should be lowered in one smooth continuous motion. Maintain directional control with rudder as long as possible, using brakes only when necessary. Utilize the full landing area, permitting



LANDING PATTERN DIAGRAM

CDC-1-37


Figure 2-2

the aircraft to roll to a stop, rather than using the brakes unnecessarily.

CROSS-WIND LANDING.

When landing in a cross-wind, normal landing procedure can be employed; however, landing in a more level attitude will make directional control easier after the aircraft is on the ground. On final approach, the up-wind wing should be lowered enough to counteract drift, while the line of flight is maintained by the application of opposite rudder. The result is a slip, equal to and opposite the effect of drift, with the longitudinal axis of the airplane in line with the runway. The slip should be held until touch-down. If it is relaxed prior to the time when the aircraft is on the runway, the purpose is defeated and the aircraft will land drifting. During the ground roll, when airspeed has decreased to approximately 60 mph (50 knots), the tail should be lowered and full back pressure applied in one smooth continuous motion. This technique provides adequate rudder control until the tail wheel is firmly on the ground. Up-wind aileron will aid in maintaining directional control on the runway. That period when the tail is lowered is the most critical and it is here that your greatest attention is required.

NIGHT FLIGHT



CDC-1-38

NIGHT LANDING.

For night landings, power approaches should be employed. The procedure for accomplishing routine checks is the same as that for a normal landing; however, by utilizing power for the entire approach, the rate-of-descent will be less, permitting an extended landing pattern. The larger approach pattern, at night, makes more apparent the position of the landing area relative to the aircraft. This aids appreciably in planning a constant rate-of-descent. It also permits "lining-up" with the runway a greater distance from the landing area where drift is more apparent and obstructions on the final approach can be more carefully scrutinized. By using power throughout the approach and into the flare-out for landings, rate-of-descent can, at any time, be sharply reduced by increasing power. This decreased rate-of-descent gives more time for accurate appraisal of distance from the ground during the flare-out and touch-down portions of the landing. Landing lights may be used at the discretion of the pilot with the following limitations:

1. Due to the initial surge of electrical current the

switches controlling the wing flaps, landing lights and landing gear, should not be turned on simultaneously.

2. Do not exceed specified maximum speed for flight with landing lights extended.

MINIMUM RUN LANDING.

In the execution of a minimum run landing, a power approach should be made to assure minimum safe clearance over obstructions. The approach end of the runway should be crossed with the aircraft in a slightly nose high attitude at 72 mph (63 knots) IAS. In this attitude and with the proper IAS, rate-of-descent is very rapid unless considerable power is used to retard it. Therefore, with power variation the remaining altitude, after obstructions are crossed, can be dissipated with a minimum forward motion. Some power will be required until the aircraft has been flared and landed in a three point attitude. As touch-down is made, the power should be "cut" and the control column pulled full back. This procedure produces a minimum touch-down speed and the aircraft can be braked to a full stop in a very short distance.

HIGH GROSS WEIGHT LANDING.

In the event of a landing at or near the maximum gross weight, you will find that characteristically the aircraft can be flown in the same manner as for a normal landing. As shown on the landing curve Appendix I, speeds are greater with the increased weight. Technique for specific results, however, remains the same.

GO-AROUND.

If at any time during the approach it becomes necessary to abandon the landing, the paramount factor is the regaining of speed for the necessary climb out. If this should occur with any appreciable amount of altitude, the procedure is simply to apply "Climb Power," establish a climbing attitude, retract the landing gear and then the flaps.

NOTE

Keep in mind that the landing gear control circuit breaker must be reset before the landing gear can be retracted.

If proximity to the ground or other object necessitates immediate pull-up, the following procedure will produce the maximum climb in the minimum period of time.

Apply Take-Off power.

Establish a climbing attitude.

Retract Landing Gear.

At a speed of 117 mph (102 knots) IAS — Retract Flaps.

In either case after climb is established, cowl flaps should be positioned for "Trail."

For procedures required in landing emergencies, refer to Section III.

AFTER LANDING.

When the landing roll has been completed, accomplish the following:

- Cowl Flap Handle — OPEN.
- Wing Flap Lever — UP.
- Manifold Heat — As required.
- Oil Shutter Levers — As required.

NOTE

If landing is made on a surface such as stone or gravel, wing flaps may be damaged when such material is thrown by the main landing wheels. For this reason, the flaps should be retracted immediately after landing.

- Fuel Booster Switches — OFF.
- Tail Wheel Handle — UNLOCKED before turning.
- Pitot Heat Switches — OFF.

POST FLIGHT ENGINE CHECK.

Complete this check prior to stopping engines.

- Ignition Switch — Check ground at 700 rpm. Turn momentarily to OFF. Engine should stop firing.
- Idle Speed and Mixture — Check (500 rpm). With engines at idle, slowly move the mixture levers toward Idle Cut-Off and throughout the operation watch the Manifold Pressure Gage. A decrease of more than $\frac{1}{4}$ -inch manifold pressure indicates an excessively rich mixture. An immediate increase in manifold pressure, not preceded by a decrease, indicates the idle mixture is too lean.

Engine power, ignition and the cruising fuel air mixture are to be checked as prescribed in the preflight engine check.

NOTE

If engine operation is found to be rough on one magneto, operate the engine on this magneto alone just prior to shut-down. This procedure will aid in isolating a cylinder which is not firing if maintenance personnel are immediately advised.

All malfunctioning controls or components should be reported on the appropriate form.

BEFORE STOPPING ENGINES.

For cold weather operation, refer to Section IX, Oil Dilution Procedure. Engines should be operated at 1200 rpm until temperatures have stabilized at their lowest reading. If it is not necessary to cool engines,

they should be operated a minimum of 1 minute to scavenge the oil system.

STOPPING ENGINES.

- Mixture Levers — IDLE CUT-OFF.
- After engines have stopped firing:
- Throttles — Slowly to FULL OPEN.
- After engines have stopped:
- All ignition switches — OFF.


BEFORE LEAVING THE AIRCRAFT.

- Wheels chocked or Parking Brake — ON.

NOTE

Brake disc warpage may occur if the parking brake is left "Locked" when hot from excessive braking.

- Battery Switches — OFF.
- Instrument Inverter Switch — OFF.
- All Light Switches — OFF.
- Flap Lever — UP (Flaps retracted)
- Left Engine Fuel Selector Handle — OFF.
- Tail Wheel Handle — LOCKED.
- Right Engine Fuel Selector Handle — OFF.
- Gyro Instruments — Caged.
- Turn-and-Bank Power Selector Switch — NORMAL.
- Flight Controls — Locked.
- Form 1 complete.



CDC-1-83

ALPHABETICAL INDEX

A

Additional — Night Flight Check List	28
After Landing Procedures	36
After Take-Off Procedures	32
Aileron & Rudder Indicators	17
Air — Cold Air Controls	47
Airspeed Position Correction	82
Airspeed — Minimum Safe Single Engine	37
Air — Turbulent Air Penetration Chart	72
All Weather Operation	71-78
Analysis — Electrical Load Charts	64-67
AN/ARC-3 Command Radio	51
AN/ARC-3 Command Radio Operation	51
AN/ARN-7 Radio Compass	51
AN/ARN-7 Radio Compass Control Light	52
AN/ARN-7 Radio Compass Operation	51
Anti-icer — Carburetor	75
Anti-icing & De-icing System	48
Anti-icing — Propeller	48
— Propeller Control	48
— Propeller Operation	48
Approaches — Instrument	73
Arrangement — General Arrangement	4
Audio Switch Panels	51
Auxiliary Equipment — Description & Operation	47-54

B

Baggage Compartment Light	52
Baggage Compartment Light Switch	52
Bail Out	44
Balance — Weight & Balance Limitations	55
Bank — Pilots Turn & Bank Power Switch	11
Bar — Master Switch	10
Battery Switches	11
Beacon Receiver	51
Marker Beacon R-122/ARN-12	51
Marker Beacon Indicators R-122/ARN-12	51
Marker Beacon Operation R-122/ARN-12	51
Before Landing Check List	33
Before Leaving Aircraft	36
Before Stopping Engines	36
Before Take-Off Check Lists	30
Booster Pumps — Fuel System Operation	63
Booster Pump Switches — Fuel	9
Booster Switch — Ignition	3
Brake — Parking Brake Handle	21
Brake System	20
Breakers — Circuit Breakers	11
Buttons — Cabin Heat	47
— Oil Bypass	6
— Propeller Feathering	3

C

Cabin Compartment Lights —	
Lavatory & Baggage	52
Cabin Dome Light Switches	52
Cabin Door Controls	24
Cabin Heat Buttons	47
Capacity — Space	58
Case — Data	53
— Flight Report	54
— Map	54
Carburetor Anti-icing	75
Carburetor Mixture Temperature Gage	3
Characteristics — Flight	61-62
Chart — Fuel Quantity Data	13
— Main Differences Table	2
— Maximum Glide	46
— Stall	62
— Turbulent Air Penetration	72
— Use of (Weight Limitations)	60
— Weight Limitations	59
Charts — Electrical Load Analysis	64-67
Checks — Normal Procedures	25
Pre-Flight	25-30
In-Flight	31-35
Post-Flight	36
Circuit Breakers	11
Climb Curve	94C
Climb Curve — Single Engine	94D
Climb — Emergency	94L
Climb — Instrument	72
Cold Air Controls	47
Cold Weather Operation	76-78
Command Radio AN/ARC-3	51
Command Radio Operation AN/ARC-3	51
Communications Equipment Table	49
Communications & Radio Equipment	51
Compass — Radio AN/ARN-7	51
Control Pressure	61
Controls — Brake System	20-21
— Cabin Door	24
— Cold Air	47
— Communications & Radio Equipment	51
— Engine Fire Extinguisher	22
— Exterior Lighting	52-53
— Flight	16-18
— Flight Control System	16
— Heating & Ducting	47
— Interior Lighting	52
— Landing Gear System	18-20
— Pitot Heat Switches	51
— Propeller Anti-icing	48
— Radio Control Panel Lighting	52

— Vacuum	16
— Windshield Wipers	53
— Wing & Tail De-icing	51
Coolers — Oil Coolers & Shutter Levers	4
Correction — Airspeed Position	82
Cowl Flap Handles	2
Crew — Minimum Crew	55
Crew Duties (Not Applicable)	69
Cross Feed Handle — Suction	9
Cross Feed — Suction	68
Cruise — Instrument Cruise	73
Curve — Take-Off	94B
Cylinder Head Temperature Gage	3

D

Data Case	53
Data — Operating	79
Deflated Tire Landings	43
Defrosting	47
De-icer — Wing & Tail	75
De-icers — Wing & Tail Control	50
De-icing & Anti-icing System	48
Descent — Checks & Operation	32
Descent — Instrument Flight	73
Desert Procedures	78
Description — Aircraft	1-24
Description & Operation of Auxiliary Equipment	47-54
Diagrams — Electrical System	14
— Emergency Equipment	21
— Emergency Equipment	38
— Exterior Inspection	26
— Fuel System	12
— G. C. A. Letdown	74
— General Arrangements	4
— Landing Pattern	34
— Landing Pattern One Engine	40
— Radio Range Letdown	73
— Servicing	23
Dilution — Oil	6
Distribution of Load	58
Ditching	44
Dome Light Switches — Cabin	52
Door — Cabin (Emergency Release Handle)	24
Drainage — Fuel Sump (Cold Weather)	78
Ducting & Heating	47
During Flight — Engine Failure	39
— Fire	42
During Take-Off Engine Failure	39
Duties — Crew (Not Applicable)	69

E

Emergency — Climb	94L
— Single Engine Climb	94M
— Electrical Power System	45
— Entrance	44
— Equipment	22
— Equipment Diagram	38

— Flap System	45
— Fuel System	44
— Hand Crank (Flaps)	18
— Hand Crank (Landing Gear)	20
— Landing Gear Clutch	20
— Landing Gear Lever Release	19
— Landing Gear System	45
— Landings	43-44
— Procedures	37-45
— Release (Cabin Door & Escape Hatch)	24
— Service Ceiling	94N
Electrical — Fire	42
— Load Analysis Charts	64
— Power System Emergency	45
— Power Supply System & Indicators	10-13
— System Diagram	14
— System Limits	55
— System Operation	68
Elevator Controls & Indicators	16-18
Elimination — Smoke	42
Endurance — Maximum	94F
Engines	1
— Cold Weather Stopping	77
— Failure & Operation	37-41
— Fire (Ground & In-Flight)	41-42
— Fuel Controls & Indicators	8-9
— Gage Units	3
— Ground Operation & Tests	29-30
— In-Flight Operation	31-35
— Instruments	3
— Limitations	55
— Post-Flight Operation & Checks	36
— Selector Switch (Starting)	2
— Single Engine Climb	94D
— Starting	28
Entrance — Emergency	44
Equipment — Description & Operation of Auxiliary Equipment	47-54
— Emergency Equipment Diagram	38
— Miscellaneous	53
— Radio & Navigation	73
— Relief	54
— Table (Communications)	49
Explanation of Weight Limitations Chart	60
Exterior Inspection	25
Exterior Lighting	53
Extinguishers & Controls — Fire	22

F

Failure — Engine	37
— Engine Failure Procedures	37-41
— Propeller	41
Feathering Buttons — Propellers	3
Feathering — Propeller	3
Filter Switches — Radio Range	51
Fire — Electrical Fire in Flight	42
— Engine Fire in Flight	42

— Engine Fire on the Ground	41
— Extinguisher Controls & Indicators	22
— Extinguisher (Engine)	22
— Extinguisher (Hand)	22
— Fuselage Fire in Flight	42
— Wing Fire in Flight	42
First Aid Kits	24
Flap Lever — Wing	18
Flaps — Cowl Flap Handles	2
— Position Indicator	18
— System Emergency	45
— Wing	18
Flight — Characteristics	61-62
— Checks (Pre-Flight)	25-30
(In-Flight)	31-35
(Post-Flight)	36
(Night-Additional)	28
— Cold Weather Operation	76-78
— Control System	16-18
— Desert Procedures	78
— Instrument Flight Operation	71-75
— Instrument Flight Radio & Navigation Equipment	73
— Report Case	54
— Turbulence & Thunderstorms	75
Fuel Booster Pump Switches	9
Fuel Flow Per Engine	92-94A
Fuel — Nautical Miles Per Engine	88-91
Fuel Pressure Drop Engine Operating	39
Fuel Quantity Data Chart	13
Fuel Selector Handles — Engine	8
Fuel System	6
— Booster Pumps (Operation)	63
— Diagram	12
— Emergencies	44
— Indicators	9
Fuel Tank Sequence	63

G

Gage — Carburetor Air Temperature	3
— Fuel System Indicators	9
— Instruments (Pitot & Static)	21-22
— Loadmeters	11
— Manifold Pressure	3
— Tab Position Indicators	17-18
— Tachometer	3
— Units (Engine)	3
— Vacuum Indicators	16
G. C. A. Letdown & Diagram	74
Gear — Landing Gear System,	
Controls & Indicators	18-20
— Landing Gear System Emergencies	45
— Limitations	60
Generators	10
— Inoperative Lights	11
— Loadmeters	11
— Switches	11
Glide — Maximum Glide Chart	46

Go Around	35
Go Around — Single Engine	41
Ground Fire	41

H

Hand Crank — Emergency Flap Operation	18
— Emergency Gear Operation	20
Hand Fire Extinguisher	22
Handles — Cowl Flap	1
— Emergency Cabin Door Release	24
— Emergency Escape Hatch Release	24
— Engine Fuel Selector	8
— Parking Brake	21
— Suction Cross Feed	9
Harness — Shoulder	24
Head Temperature Gage — Cylinder	3
Heat — Cabin Heat Buttons	47
— Carburetor Anti-icing	75
— Levers (Manifold)	1
— Pilot Compartment Outlet Shut-Off	47
— Pitot Heater, Switches & Operation	51
Heating & Ducting & Windshield Defrosting	47
High Weight Landing	35
Holding — Instrument Flight	73

1

Ice, Snow & Rain	74
Icing — Anti-icing & De-icing Equipment	
Controls & Operation	47-51
— Carburetor Anti-icing	75
— Pitot Anti-icing	51
— Propeller Anti-icing	48
— Windshield Defrosting	47
— Wing & Tail De-icer	75
— Wing & Tail De-icing	50
Ignition Booster Switch	3
Ignition Switches	2
Indicators — Aileron & Rudder	17
— Elevator	18
— Engine	3
— Engine	56-57
— Engine Fire Extinguisher	22
— Flap Position	18
— Flight Tab Position	17
— Fuel System	9
— Generator Inoperative Lights	11
— Instruments	21
— Landing Gear Position	20
— Marker Beacon Receiver	
R-122/ARN-12	51
— Radio Compass AN/ARN-7	51
— Vacuum System	16
In Flight — Cold Weather Operation	77
— Electrical Fire	42
— Engine Failure	39
— Engine Fire	42
— Fuselage Fire	42
— Operational Instruction Charts	82-93

— Propeller Failure	41
— Restarting Engine	39
— Turbulence & Thunderstorms	75
— Wing Fire	42
Inoperative Lights — Generators	11
Inspection — Before Exterior	25
— Before Leaving Aircraft	36
— Exterior	25
— Exterior Inspection Diagram	26
— Interior	27
— Night Flight (Additional)	28
Instructions — Taxiing	30
Instruments	21
— Engine	3
— Flap Position Indicators	18
— Fuel System	9
— Inverter	11
— Inverter Switch	13
— Landing Gear Position Indicators	20
— Lighting Control	53
— Markings	56
— Radio Compass AN/ARN-7	51
— Static & Pitot Pressure	22
Instrument Flight	71-74
— Approaches & Diagrams	73-74
— Climb	72
— Cruising Flight	73
— Descent	73
— Holding	73
— Radio & Navigation Equipment	73
— Take-Off	71
Interior Heating & Windshield Defrosting	47
Interior Lighting	52-53
Interphone RC-36	51
Interphone Selector Switch & Volume Control	51
Inverter — Instrument	11
Inverter — Instrument Inverter Switch	13

J

K

Kits — First Aid	24
Kits — Mooring	54

L

Landing — After Landing Checks	36
— Before Leaving Aircraft Checks	36
— Characteristics	61
— Cold Weather	77
— Cross Wind	34
— Curve	94E
— Emergencies (Deflated Tires, Unprepared Runways & Wheels Up)	43-44
— High Weight	35
— Minimum Run	35

— Night	33
— Normal	35
— Pattern	34
— Pattern (One Engine)	40
— Single Engine	40
— With No Power	41
Landing Gear — Controls & Operation	18-20
— Emergency Clutch	20
— Emergency Hand Crank	20
— Lever	19
— Lever Emergency Release	19
— Limitations	60
— Malfunction Light	19
— Position Indicators	20
— System Emergency	45
— Tail Wheel Lock System & Control	20
— Warning Horn & Silencer	20
Landing Lights — Limits	55
— Switch	53
Lavatory & Baggage Compartment Lights	52
Leaning — Manual Leaning	63
Letdowns — G. C. A. Letdown & Diagram	74
— Radio Range Letdown & Diagram	73-74
Levers — Cowl Flaps	2
— Landing Gear	19
— Manifold Heat	1
— Mixture	1
— Oil Cooler Shutters	4
— Propeller	3
— Shoulder Harness Locking	24
— Throttle	1
— Wing Flap	18
Liaison Radio Selector Switch	51
Lighting — Control (Instruments)	53
— Equipment	52
— Exterior	53
— Interior	52
— Pilot's Compartment	52
— Radio Control Panel	52
Lights — Generator Inoperative	11
— Landing Gear Malfunction	19
— Landing Lights Limits	55
— Lavatory & Baggage Compartment	52
Light Switches — Cabin Dome	52
— Landing Lights	53
— Map Reading	52
— Navigation Lights	53
— Passing Light	53
— Radio Controls Spotlight Rheostat Switch	53
— Taxi Lights	53
— Utility Light	52
Limitations — Electrical System	55
— Engine	55
— Landing Gear	60
— Landing Lights	55
— Performance	60
— Operating	55-60
— Operating Weight	55

— Weight & Balance	55
— Weight Limitations Chart	59
— Wing	58
Load Analysis Charts — Electrical	64
Load Distribution	58
Load Factors & Margin of Safety	58
Loadmeters	11
Lock — Flight Control	16
Locking Lever — Shoulder Harness	24
Long Range Prediction Graphs	94G-94K

M

Main Differences Table	2
Malfunction Light — Landing Gear	19
Maneuvers Prohibited	55
Manifold Heat Levers	1
Manifold Pressure Gage	3
Manual Leaning	63
Map Case	53
Map Reading Light & Switches	52
Margin of Safety & Load Factors	58
Marker Beacon Receiver	
R-122/ARN-12	51
Marker Beacon Receiver Indicator & Operation R-122/ARN-12	51
Markings — Instrument	56
Master Switch Bar	10
Maximum Endurance	94F
Maximum Glide Chart	46
Minimum Crew	55
Minimum Run Landing	35
Minimum Run Take-Off	32
Minimum Safe Single Engine Airspeed	37
Miscellaneous Equipment	53
Mixture — Carburetor Air Temperature Gage	3
Mixture Levers	1
Mooring Kit	54

N

Nautical Miles Per Pound of Fuel Graphs	88-91
Navigation Lights Switch	53
Navigation & Radio Equipment (Instrument Flight)	73
Night Flight Check — Additional	28
Night Landing	35
No Power Available Landing	41
Normal Flight	32-33
— Landing	33
— Procedures	25-36
— Take-Off	31

O

Oil Bypass Buttons	6
Oil Coolers	4
Oil Cooler Shutter Levers	4
Oil Dilution Switches	6
Oil System	3
One Engine Landing Pattern	40

Operating Data	79-93
Operating Limitations	55-60
Operating Weight	58
— Limitations	55
— Limitations Chart	59
Operation — All Weather	71-78
— Anti-icing & De-icing Equipment	74-75
— Cold Weather	76-78
Operation & Description of Emergency Equipment	47-54
Operation — Desert Procedures	78
— Electrical System	68
— Emergency Operations	37-45
— Engine Ground Operation	29
— Fuel System	63
— Instrument Flight	71-74
— Normal Operation	25-36
— Pitot Heat	51
— Propeller Anti-icing	48
— Radios	51-52
— Systems Operation	63-68
— Turbulence & Thunderstorms	75
Outlet Shut-Off — Pilots Compartment Air	47
Overvoltage Relay	11

P

Panel — Radio Control Lighting	52
Panels — Audio Switch	51
Parking Brake Handle	21
Parking — Cold Weather	78
Passing Light Switch	53
Passenger Seats	54
Pattern — Landing	34
— Landing (One Engine)	40
Penetration — Turbulent Air Chart	72
Performance Limitations	60
Pilots Compartment — Air Outlet Shutoff	47
— Lighting	52
Pitot Heater Switches & Operation	51
Pitot & Static Pressure Source	22
Position Indicators — Flap	18
— Flight Tab	17-18
— Landing Gear	20
Post Flight Check	36
Power Change	63
Power — Electrical Supply System	10
Power — No Power Landing	41
Power Schedules	83-87
Power Switch — Pilots Turn & Bank	11
Power System Emergency — Electrical	45
Prediction Long Range	94G-94K
Pressure — Control Pressure	61
Pressure Drop Engines Operating Normally — Fuel	39
Pressure — Manifold Pressure Gage	3
Pressure Source — Pitot & Static	22
Procedures — All Weather	71-78
— Bail Out	44
— Cold Weather	76-78

— Crash Landing	41	Selector Switch & Volume Control Interphone	51
— Desert	78	Servicing Diagram	23
— Ditching	44	Shoulder Harness Locking Levers	24
— Emergency	37-45	Shutter Levers — Oil Coolers	4
— Fire	41-42	Silencer — Warning Horn	20
— Instrument Flight	71-73	Single Engine — Climb Curve	94D
— Landing Emergencies	43-44	— Emergency Climb	94M
— Let Down	73-74	— Go Around	41
— Normal Operating	25-36	— Landing	40
— Single Engine	38	— Procedures	38
— Systems Emergencies	44-45	— Safe Minimum Airspeed	37
— Turbulence & Thunderstorms	75	Smoke Elimination	42
Prohibited Maneuvers	55	Snow, Ice & Rain	74
Propellers	3	Source — Pitot & Static Pressure	22
— Anti-icing, Control & Operation	48	Space — Capacity	58
— Failure	41	Spins	61
— Feathering	3	Spotlight Rheostat — Radio Controls Light	53
— Feathering Buttons	3	Stability	61
— Icing	74	Stall Chart	62
— Levers	3	Stalls	61
Pumps — Fuel Booster	63	Starter Switch	3
— Fuel Booster Switches	9	Starting — Cold Weather	76
		— Engines	28
		— Engine Selector Switch	2
		— System	2
		Static & Pitot Pressure Source	22
		Stopping Engines	36
		— Before Stopping Engines	36
		— Cold Weather	77
		Suction Cross Feed	68
		Suction Cross Feed Handle	9
		Sump Drainage — Fuel (Cold Weather)	78
		Supply — Electrical Power System	10
		Switches — Battery	11
		— Cabin Dome Lights	52
		— Engine Starting Selector	2
		— Filter (Range)	51
		— Fuel Booster Pump	9
		— Generator	11
		— Ignition	2
		— Ignition Booster	3
		— Instrument Inverter	13
		— Landing Lights	53
		— Lavatory & Baggage	
		— Compartment Lights	52
		— Map Reading Lights	52
		— Master Bar	10
		— Navigation Lights	53
		— Oil Dilution	6
		— Passing Light	53
		— Pilots Turn & Bank Power	11
		— Pitot Heater	51
		— Primer	3
		— Starter	3
		— Selector & Volume Control	
		— (Interphone)	51
		— Taxi Lights	53
		— Utility Lights	52
		— Voltmeter	11
		Switch Panels — Audio	51

Q

Quantity — Fuel Data Chart	13
----------------------------	----

R

Radar Letdown & Diagram — G. C. A.	74
Radio & Communications Equipment	51
Radio Compass & Operation AN/ARN-7	51
Radio Control Panel Lighting	52
Radio Controls Spotlight Rheostat Switch	53
Radio & Navigation Equipment	
(Instrument Flight)	73
Radio Operation	51
Radio Range Letdown	74
Radio Range Letdown Diagram	73
Rain, Ice & Snow	74
Reading Light Switches — Map	52
Receiver Indicators	51
Relay — Overvoltage	11
Release — Cabin Door Emergency Handle	24
— Emergency Escape Hatch Handle	24
— Landing Gear Lever Emergency	19
Relief Equipment	54
Restarting Engine in Flight	39
R-122/ARN-12 Marker Beacon	
Receiver, Indicators & Operation	51
Rudder & Aileron Indicators	17
Runways — Landing on Unprepared Runways	43

S

Safe Minimum Airspeed — Single Engine	37
Safety & Load Factors — Margin	58
Seats	24
Seats — Passenger	54
Selector Handles — Engine Fuel	8
Selector Switch — Engine Starting	2

Systems — Anti-icing & De-icing	48
— Brake	20
— Electrical Limits	55
— Electrical Power Supply	10
— Flight Control	16
— Fuel	6
— Fuel Indicators	9
— Interior Heating & Windshield Defrosting	47
— Landing Gear	18
— Oil	3
— Starting	2
— Tail Wheel Lock & Control	20
— Vacuum	16
— Ventilation	47
Systems Diagrams — Electrical	14
— Fuel	12
Systems Emergencies — Electrical Power	45
— Flap	45
— Fuel	44
— Landing Gear	45
Systems Operation	63-68
— Electrical	68
— Fuel	63

T

Tab — Flight Controls	16
Tab — Position Indicators	17
Table — Communications Equipment	49
— Main Differences	2
Tachometer	3
Tail Wheel Lock System & Control	20
Tail & Wing De-icer	75
Tail & Wing De-icers	50
Take-Off — After	32
— Before	30
— Chart	83
— Climb Over Obstruction	32
— Cold Weather	77
— Cross Wind	31
— Curve	94B
— Desert	78
— Engine Failure	39
— Instrument	71
— Minimum Run	32
— Night	32
— Normal	31
Tank Sequence — Fuel	63
Taxiing — Cold Weather	77
— Instructions	30
Taxi Lights Switch	53
Temperature Gages — Carburetor Air	3
— Cylinder Head	3

Tests — Engine Ground	29
Throttle Levers	1
Tires Deflated Landings	43
Traffic & Pre-Traffic Pattern Checks	33
Turbulence & Thunderstorms Flight	75
Turbulent Air Penetration Chart	72
Turn & Bank — Pilots Power Switch	11

U

Units — Engine Gage	3
Use of the Charts & Problem (Flight Operation Instructions)	80
Use of the Chart (Weight Limitations)	60
Utility Light Switches	52

V

Vacuum System, Control & Indicators	16
Vent & Heat Diagram	48
Ventilation System	47
Voltage — Overvoltage Relay	11
Voltmeter Switch	11
Volume Control — Interphone	51

W

Warning Horn — Landing Gear	20
— Silencer	20
Weather — All Weather Operation	71-78
— Cold Weather Operation	76-78
— Desert Operation	78
Weight & Balance Limitations	55
Weight — Distribution	58
— Gross	58
— Limitations	55
— Limitations Chart	59
— Operating	58
Wheels — Landing Gear System, Controls & Operation	18-20
Wheels — Landing With Deflated Tires	43
Wheels Up Landing	44
Wind — Crosswind Landing	34
— Take-Off	31
Windshield Defrosting System	47
Windshield Wipers	53
Wing Flaps & Lever	18
Wing Limitations	58
Wing & Tail De-icer	75
Wing & Tail De-icers	50
Wipers — Windshield	53

X - Y - Z