

CDC-1-46

section IV

DESCRIPTION AND OPERATION OF AUXILIARY EQUIPMENT

INTERIOR HEATING AND WINDSHIELD DEFROSTING SYSTEM.

GENERAL

Heated air is furnished the aircraft interior by two identical systems, each with its own control. One system supplies air to all outlets on one side of the aircraft, the other system to the other side. Each engine is the source of heat for the corresponding system. There are no means for providing heat to either the cabin area or the pilot's compartment separately.

With the understanding that both heating systems are identical, the operation of only one side will be discussed in detail.

HEATING AND DUCTING. Outside air enters the system through an air intake which is located in the nacelle in such position that will pick up clean outside air. It is then heated by the engine exhaust, utilizing a heat exchanger. Two ducts lead from the nacelle; one to a cabin outlet which is located near the floor between the seats, the other to the pilot's compartment. Two outlets are provided in the pilot's compartment, one on the side of the aircraft forward of the seat; the other, for defrosting, at the base of the windshield.

NOTE

With propeller anti-ice operating, alcohol fumes will be picked up by the heating system and will become quite noticeable in the cabin.

CABIN HEAT BUTTONS.

Control valves, located in the nacelles are operated by push-pull buttons (figure 1-5) on the pedestal. This button incorporates a locking device, for maintaining the desired setting, which should be released by depressing the center plunger before repositioning.

With the pedestal button full out all of the heated air is dumped overboard; full in, all the heated air is directed into the cabin and pilots' compartment. Any intermediate position will direct a proportional amount of heated air to the aircraft interior.

For that portion of the air which flows to the cabin, there is no further control.

PILOT COMPARTMENT OUTLET SHUT-OFF.

The outlet forward of the pilot's seat is equipped with a combined deflector and shut-off valve. The outlet is in the OFF position when the opening is pointed aft. Turning counterclockwise it begins opening, reaching a full open position after approximately 90 degrees and remaining full open until the forward position where it begins to close. All air which does not pass through this outlet will be directed to the windshield defrost outlet. So remember, **MAXIMUM DEFROSTING HEAT IS OBTAINED WITH THE PILOTS' COMPARTMENT OUTLETS CLOSED.**


VENTILATION SYSTEM.

Cold air for ventilation enters the leading edge of the wing between the nacelle and the fuselage and passes through a duct to the cold air control valve in the wall of the pilots' compartment. From here it is ducted to the individual outlets in the cabin and to the pilot's and co-pilot's outlets. Individual and identical systems are provided on each side of the fuselage and are individually controlled.

Overhead exhaust vents are provided in the pilots' compartment and in the cabin section to permit the escape of air from the aircraft.

COLD AIR CONTROLS.

The cold air control valve (figure 4-1) is a screw-type valve located to the rear of each pilot's seat on the cabin wall. Turning the valve clockwise closes



HEATING AND VENTILATING SYSTEM

Figure 4-1

off the air flow and counterclockwise increases flow. The individual outlets located by each pilot's seat just ahead of the control valve and one above and ahead of each passenger seat are the same in operation as the pilot's and copilot's individual hot air outlets, in that they may be used for deflecting or shutting off air flow.

ANTI-ICING AND DEICING SYSTEMS.

PROPELLER ANTI-ICING.

The propellers are equipped with a liquid type anti-ice system. Both propellers are anti-iced simultaneously from a single supply tank through a single pump. The flow is from the 3 gallon tank, located on the floor boards behind the pilot's seat, through check valves in the nacelles and into the slinger rings on the propeller hubs.











PROPELLER ANTI-ICE CONTROL. The propeller

anti-icing fluid pump, and thus the rate of flow, is controlled by the rheostat (figure 1-8) on the right subpanel. As the knob is turned in a clockwise direction from the OFF position, the maximum rate of flow (approximately 35 minutes' supply) is obtained as the pump starts to operate. Continued turning of the rheostat in a clockwise direction decreases the rate of flow to a minimum (approximately 3½ hours' supply). The maximum travel of the rheostat is approximately 270 degrees.

PROPELLER ANTI-ICE OPERATION. The normal operating position is indicated by a rectangular block with the word NORMAL on it across the placarded arrow. This setting affords approximately 3 hours' supply of fluid. The propeller anti-icing system is designed to prevent the formation of ice, not to remove it after it has formed.

Refer to Servicing Diagram for fluid specifications.

Figure 4-2. Communications Equipment Table

DESIGNATION	TYPE	FUNCTION	PRIMARY OPERATOR	RANGE	LOCATION OF CONTROLS	ON-OFF PROCEDURE
 RC-36 INTERPHONE	Interphone Equipment	Intercommunication Between Pilots and Passengers	Crew Members	Stations Within The Airplane	Jack Box Installation Near Each Pilot's Seat and on the Right Hand Cabin Wall.	BATTERY  ON OFF SWITCHES
 AN ARC-27	VHF Command Set	Short Range Two-Way Voice and Code Communication	Pilot and Copilot	Line of Sight	Radio Control Panel Overhead Between Pilot and Copilot	 ON OFF
 BC 453-B	Low Frequency Receiver	Radio Navigation	Pilot and Copilot	20-200 Miles, Depending on Frequency Used and Time of Day	Radio Control Panel Overhead Between Pilot and Copilot	 ON OFF
 BC 1333 OR R 122 ARN-12	Marker-Beacon Receiver	Receives Location Marker Signal on Navigational Beam	Pilot and Copilot	Airplane to Ground		BATTERY  ON OFF SWITCHES
 R 122 ARN-12	Radio Compass	Receive Voice and Code Signals for Homing and Direction Finding	Pilot and Copilot	20-200 Miles, Depending on Frequency Used and Time of Day	Radio Control Panel Overhead Between Pilot and Copilot	 ANT. COMP LOOP CONT OFF

T. O. 1C-45H-1

Section IV

COMMUNICATION EQUIPMENT





Figure 4-3. Communications Equipment

NOTE

With the heating system in operation, alcohol fumes will be noticeable in the cabin.

WING AND TAIL DEICER.

The leading edges of the wings and the horizontal

tail surfaces are equipped with pneumatic deicer boots. Pressure for operation is taken from the exhaust side of the engine driven vacuum pumps.

WING AND TAIL DEICER CONTROL. A push-pull button (figure 1-8) for the control of the wing and tail deicers is mounted on the right subpanel. The button is self locking so the center plunger should be depressed when the control is repositioned. There are two operating positions; full OUT directs pressure into the deicing system and also actuates an electrically driven cycling valve which further directs the pressure to the various cells within the deicer boots. With the button full IN, the cycling operation is stopped and the air is dumped overboard.

CAUTION

If at any time in flight with the deicer system not in operation a rippling of the boots is noticed, they should be inspected upon landing and replaced if necessary. A rippling or loose boot is a flight hazard and may cause failure of the skin.

WARNING

Do not attempt to land or take-off with deicer in operation. The boot changes the shape of the airfoil as it inflates and deflates. If the airplane is flown near stalling speed

with the boot in operation, a stall may result.

PITOT HEATER.

A conventional electrically heated head is used on the pitot tubes.

PITOT HEATER SWITCHES.

Two toggle switches (figure 1-7) on the left subpanel complete the circuits to the heating elements in the pitot heads; the left switch for the left pitot tube and the right switch for the right tube.

PITOT HEAT OPERATION.

Whenever possible, conditions which may cause ice to form in the pitot tubes should be anticipated so that the heater may be turned on in advance, to preclude even temporary instrument failure.

CAUTION

Prolonged ground operation of the pitot heaters will result in excessive pitot head temperatures with possible failure of the heating elements.

COMMUNICATION AND ASSOCIATED RADIO EQUIPMENT.

GENERAL.

Equipment for radio navigation as well as communication is provided in the aircraft. The various items which comprise this equipment are located in the lavatory compartment, but all controls are grouped in the overhead control panel in the pilots' compartment.

AUDIO SWITCH PANELS. Each pilot station is equipped with audio switch panel for the purpose of selecting those particular receivers to which he wishes to listen. Any number of switches may be placed ON for simultaneous reception if desired. All switches are clearly placarded as to the equipment they serve with the exception of that marked MIXED SIGNAL which serves to connect all receivers to the headset simultaneously.

FILTER SWITCHES. Each pilot station has installed conventional range filter switches.

COMP - LIAISON - COMM AND INTER - CALL SWITCH AND VOLUME CONTROL. This unit is installed for each pilot to have supplemental individual control of volume and as an interphone selector and call switch.

RC-36 INTERPHONE.

This unit is installed to provide interphone communication throughout the aircraft. It has no separate controls of its own and is on whenever the battery switches are on.

BC 1333 or R-122/ARN-12 MARKER BEACON RECEIVER. This receiver covers a range of 62 to 78 megacycles with a preset circuit for reception of the 75 megacycle fan marker, "Z" marker and ILS localizer marker signals.

BC 1333 or R-122/ARN-12 RECEIVER INDICATORS. An indicator light (figure 1-8) on the instrument panel will light in response to signal reception. This is in addition to the aural signal which may or may not be selected.

BC 1333 or R-122/ARN-12 OPERATION. No separate and individual controls are provided for this equipment since it is in operation whenever battery power is available to the bus.

AN/ARC-27 COMMAND.

This equipment provides VHF Communication from aircraft to aircraft or aircraft to ground through a frequency range of 100 to 156 megacycles. The set has line of sight range, with eight preset channels.

AN/ARC-27 OPERATION.

VHF Master Switch — ON.

VHF Channel Selector Switch — Desired frequency. Allow 45 seconds for warm-up.

Adjust volume.

To transmit — Press microphone button and speak.

To receive — Release microphone button.

To transmit code — Use D/F TONE button on the VHF panel as a key. (Limit your speed.)

To turn off set — Move Master Switch to — OFF.

AN/ARN-7 RADIO COMPASS.

The AN/ARN-7 radio compass provides for visual and aural radio navigation as well as ordinary radio reception through a frequency range of 100 to 1750 kcs. At your discretion either automatic or manual direction finding procedures may be followed.

AN/ARN-7 RADIO COMPASS OPERATION.

To operate as an ordinary receiver:

Function switch on ANT.

Frequency Selector Switch to desired band.

Volume Control — Adjust.

Tuning Crank — Tune to maximum audio level on the chosen station.

To operate as direction finding or homing equipment manually:

Function switch — ANT.

Frequency Selector Switch — Desired Band.

Volume Control — Adjust.

Tuning Crank — Tune to the maximum audio level and identify the desired stations.

CW Switch on CW.

Retune the receiver for maximum audio level.

Function Switch — LOOP.

Retune for maximum audio level.

Proceed with desired loop operation.

To operate as automatic direction finding equipment:

Function Switch — ANT.

Select the desired frequency band.

Tune to and identify the desired station.

Adjust volume.

CW Switch — CW.

Retune to greatest deflection of the tuning indicator needle.

Function Switch — COMP.

Proceed with automatic DF navigation.

BC 453-B RECEIVER.

This receiver provides for voice and code reception through a frequency range of 190 to 550 kilocycles.

BC 453-B OPERATION.

Range Receiver Switch — MCW.

Adjust volume.

Tune and identify the desired station.

NOTE

For code reception, place the Range Receiver Switch in the CW position, then tune for the highest audio level. This position may also aid in tuning stations, that are very weak, for voice reception. After attaining maximum audio level, if the switch is returned to MCW, it should be the best tuning for voice reception.




Figure 4-4

RADIO CONTROL PANEL LIGHTING.

On the left side of the radio control panel, a rheostat (figure 4-3) is provided for the control of edge lighting in the VHF and range receiver control panels. The AN/ARN-7 control panel incorporates its own lighting control, with a HI-OFF-LO toggle switch.

In addition to the lighting provided within the panels, a spotlight (figure 4-4) is located on the bulkhead below the threshold of the pilots' compartment. This

light illuminates all the radio controls with any intensity of light desired. Mounted adjacent to the light is a rheostat for its control.

LIGHTING EQUIPMENT.**INTERIOR LIGHTING.**

In addition to those radio panels which have interior panel lights, the following lighting is provided in the aircraft:

CABIN, LAVATORY AND BAGGAGE COMPARTMENT LIGHTS.

Dome lights are provided in the cabin, lavatory and baggage compartments. The three overhead lights in the cabin will furnish either white or red lighting, while the single fixtures in the lavatory and nose baggage compartment are white only.

LAVATORY AND BAGGAGE COMPARTMENT LIGHT SWITCHES. The overhead lights in the lavatory and baggage compartment are operated by toggle switches adjacent to the lights.

CABIN DOME LIGHT SWITCHES. The white lamps in all three cabin dome lights are controlled by a single two position switch (figure 1-7) on the left subpanel. The red lamp in each dome light is controlled by a two position toggle switch. The switch for the forward light is on the right hand cabin wall, above the window and forward of the front seat. The middle light switch is similarly located above the rear seat while the rear switch is on the rear cabin bulkhead.

PILOT COMPARTMENT LIGHTING.

A utility light is mounted above each seat to serve as a reading light. For greater utility, these lights are on six foot extension cords and may be pulled from their mounting brackets when advantageous. The utility lights have a clear lamp but are furnished with an attached red filter which may be clipped over the lens when necessary.


White map reading lights (figure 4-5) are mounted overhead on each side of the pilot compartment and provide illumination of the entire area.

A spotlight (figure 4-4) is located on the bulkhead below the threshold of the pilot's compartment for lighting all the radio controls with any intensity of light desired.

All instruments are individually lighted with shaded red lamps and are arranged on three separate circuits so the desired intensity of each group may be obtained. The pilot's flight instrument lights are on one circuit, the engine instruments and subpanel lights are on a separate circuit and the copilot's flight instruments on a third circuit.

UTILITY LIGHT SWITCHES. Snap switches for control of the utility lights are provided within the light housing and operated by a knob on the side.

MAP READING LIGHTS SWITCHES. Two position toggle switches are provided on the map reading light fixtures for individual control.



PILOT'S MAP READING LIGHT

CDC-1-51

Figure 4-5

RADIO CONTROLS SPOTLIGHT RHEOSTAT. Adjacent to the radio controls spotlight, on the bulkhead, is a rheostat which serves not only to control the intensity of the light but also to turn it off and on.

INSTRUMENT LIGHTING CONTROL. Each of the three groups of instrument lights are provided with its own rheostat which not only controls intensity but also serves as an on-off switch. The rheostat for the pilot's flight instruments is located on the left side of the instrument panel; the rheostat for the engine instruments and the subpanels is adjacent to the one for the pilot's flight instruments; and the one for the copilot's flight instruments is on the right side of the instrument panel. All of these knobs can be located on figure 1-9.

EXTERIOR LIGHTING.

Exterior lighting consists of conventional navigation lights, a passing light, two taxi lights, fuselage clearance lights and two landing lights. The passing light is mounted in the leading edge of the left wing, the taxi lights in the nose and the landing lights are retractable into the lower surface of each wing. The clearance lights are mounted one on the top and one on the bottom of the fuselage.

NAVIGATION LIGHTS SWITCH. Both the navigation and the clearance lights are operated by the navigation

lights switch (figure 1-7) on the left subpanel. The switch, a three position toggle, is placarded **FLASHER-OFF-STEADY** and when in the **STEADY** position, all lights burn continuously. In the **FLASHER** position, operation of the clearance lights remains continuous but the navigation lights are alternately on and off.

NOTE

If the automatic flashing device should fail while in operation, it is designed to fail safe and the lights will automatically revert to steady operation.

PASSING LIGHT SWITCH. The passing light is operated by a two position toggle switch (figure 1-7) on the left subpanel.

TAXI LIGHTS SWITCH. A two position toggle switch (figure 1-7) on the left subpanel operates the taxi lights.

LANDING LIGHTS SWITCHES. Each landing light is operated by two toggle switches. One, a three position switch, is placarded **RETRACT-OFF-EXTEND**; its purpose is obvious. During extension or retraction, the light may be stopped in any position by moving the switch to **OFF**. The other, a two position switch, is for turning the lamp off and on. The lamp may be turned on at any time except when the light is fully retracted. All four switches are together, on the left subpanel, as seen in figure 1-7.

CAUTION

Only in case of extreme emergency should the landing lights be used for ground operation. Due to the slow speed of the aircraft during ground operation, the flow of cooling air is insufficient to provide adequate cooling of the landing lights; thus overheating of the lamp filament will result in its burning out.

MISCELLANEOUS EQUIPMENT.

WINDSHIELD WIPERS.

The electrically operated windshield wipers are designed and installed for use during take-off and landing. They should not be turned on in flight, except in an emergency, since they are relatively ineffective at cruising speed and the air loads imposed on them could cause damage to the operating mechanism.

They are controlled by the windshield wiper switch (figure 1-8) on the right subpanel which is a fixed position toggle switch having **FAST-OFF-SLOW**, position, the center position being **OFF**.

CAUTION

Do not operate windshield wipers on dry glass. Such action can severely damage the linkage as well as scratching the windshield.

DATA CASE.

A data case is provided on the lavatory door.

FLIGHT REPORT CASE.

An airplane flight report case is mounted on the back of the copilot's seat.

MAP CASE.

A map case is located on the wall to the left of the pilot's seat. The case rests on the floor.

PASSENGER SEATS.

Four bucket type seats are provided in the cabin section. The seats are provided with foam rubber


cushions, safety belts and fixed type G-1 shoulder straps.

MOORING KIT.

A mooring kit is stowed on the floor of the lavatory compartment.

RELIEF EQUIPMENT.

A relief tube is provided for the pilot's comfort. When not in use, it is stowed in a clip under the pilot's seat. For the passengers, there is provided in the lavatory compartment, a chemical-type toilet and relief tube.



CDC-1-84

ALPHABETICAL INDEX

A

Additional — Night Flight Check List	28
After Landing Procedures	36
After Take-Off Procedures	32
Aileron & Rudder Indicators	17
Air — Cold Air Controls	47
Airspeed Position Correction	82
Airspeed — Minimum Safe Single Engine	37
Air — Turbulent Air Penetration Chart	72
All Weather Operation	71-78
Analysis — Electrical Load Charts	64-67
AN/ARC-3 Command Radio	51
AN/ARC-3 Command Radio Operation	51
AN/ARN-7 Radio Compass	51
AN/ARN-7 Radio Compass Control Light	52
AN/ARN-7 Radio Compass Operation	51
Anti-icer — Carburetor	75
Anti-icing & De-icing System	48
Anti-icing — Propeller	48
— Propeller Control	48
— Propeller Operation	48
Approaches — Instrument	73
Arrangement — General Arrangement	4
Audio Switch Panels	51
Auxiliary Equipment — Description & Operation	47-54

B

Baggage Compartment Light	52
Baggage Compartment Light Switch	52
Bail Out	44
Balance — Weight & Balance Limitations	55
Bank — Pilots Turn & Bank Power Switch	11
Bar — Master Switch	10
Battery Switches	11
Beacon Receiver	51
Marker Beacon R-122/ARN-12	51
Marker Beacon Indicators R-122/ARN-12	51
Marker Beacon Operation R-122/ARN-12	51
Before Landing Check List	33
Before Leaving Aircraft	36
Before Stopping Engines	36
Before Take-Off Check Lists	30
Booster Pumps — Fuel System Operation	63
Booster Pump Switches — Fuel	9
Booster Switch — Ignition	3
Brake — Parking Brake Handle	21
Brake System	20
Breakers — Circuit Breakers	11
Buttons — Cabin Heat	47
— Oil Bypass	6
— Propeller Feathering	3

C

Cabin Compartment Lights —	
Lavatory & Baggage	52
Cabin Dome Light Switches	52
Cabin Door Controls	24
Cabin Heat Buttons	47
Capacity — Space	58
Case — Data	53
— Flight Report	54
— Map	54
Carburetor Anti-icing	75
Carburetor Mixture Temperature Gage	3
Characteristics — Flight	61-62
Chart — Fuel Quantity Data	13
— Main Differences Table	2
— Maximum Glide	46
— Stall	62
— Turbulent Air Penetration	72
— Use of (Weight Limitations)	60
— Weight Limitations	59
Charts — Electrical Load Analysis	64-67
Checks — Normal Procedures	25
Pre-Flight	25-30
In-Flight	31-35
Post-Flight	36
Circuit Breakers	11
Climb Curve	94C
Climb Curve — Single Engine	94D
Climb — Emergency	94L
Climb — Instrument	72
Cold Air Controls	47
Cold Weather Operation	76-78
Command Radio AN/ARC-3	51
Command Radio Operation AN/ARC-3	51
Communications Equipment Table	49
Communications & Radio Equipment	51
Compass — Radio AN/ARN-7	51
Control Pressure	61
Controls — Brake System	20-21
— Cabin Door	24
— Cold Air	47
— Communications & Radio Equipment	51
— Engine Fire Extinguisher	22
— Exterior Lighting	52-53
— Flight	16-18
— Flight Control System	16
— Heating & Ducting	47
— Interior Lighting	52
— Landing Gear System	18-20
— Pitot Heat Switches	51
— Propeller Anti-icing	48
— Radio Control Panel Lighting	52

— Vacuum	16
— Windshield Wipers	53
— Wing & Tail De-icing	51
Coolers — Oil Coolers & Shutter Levers	4
Correction — Airspeed Position	82
Cowl Flap Handles	2
Crew — Minimum Crew	55
Crew Duties (Not Applicable)	69
Cross Feed Handle — Suction	9
Cross Feed — Suction	68
Cruise — Instrument Cruise	73
Curve — Take-Off	94B
Cylinder Head Temperature Gage	3

D

Data Case	53
Data — Operating	79
Deflated Tire Landings	43
Defrosting	47
De-icer — Wing & Tail	75
De-icers — Wing & Tail Control	50
De-icing & Anti-icing System	48
Descent — Checks & Operation	32
Descent — Instrument Flight	73
Desert Procedures	78
Description — Aircraft	1-24
Description & Operation of Auxiliary Equipment	47-54
Diagrams — Electrical System	14
— Emergency Equipment	21
— Emergency Equipment	38
— Exterior Inspection	26
— Fuel System	12
— G. C. A. Letdown	74
— General Arrangements	4
— Landing Pattern	34
— Landing Pattern One Engine	40
— Radio Range Letdown	73
— Servicing	23
Dilution — Oil	6
Distribution of Load	58
Ditching	44
Dome Light Switches — Cabin	52
Door — Cabin (Emergency Release Handle)	24
Drainage — Fuel Sump (Cold Weather)	78
Ducting & Heating	47
During Flight — Engine Failure	39
— Fire	42
During Take-Off Engine Failure	39
Duties — Crew (Not Applicable)	69

E

Emergency — Climb	94L
— Single Engine Climb	94M
— Electrical Power System	45
— Entrance	44
— Equipment	22
— Equipment Diagram	38

— Flap System	45
— Fuel System	44
— Hand Crank (Flaps)	18
— Hand Crank (Landing Gear)	20
— Landing Gear Clutch	20
— Landing Gear Lever Release	19
— Landing Gear System	45
— Landings	43-44
— Procedures	37-45
— Release (Cabin Door & Escape Hatch)	24
— Service Ceiling	94N
Electrical — Fire	42
— Load Analysis Charts	64
— Power System Emergency	45
— Power Supply System & Indicators	10-13
— System Diagram	14
— System Limits	55
— System Operation	68
Elevator Controls & Indicators	16-18
Elimination — Smoke	42
Endurance — Maximum	94F
Engines	1
— Cold Weather Stopping	77
— Failure & Operation	37-41
— Fire (Ground & In-Flight)	41-42
— Fuel Controls & Indicators	8-9
— Gage Units	3
— Ground Operation & Tests	29-30
— In-Flight Operation	31-35
— Instruments	3
— Limitations	55
— Post-Flight Operation & Checks	36
— Selector Switch (Starting)	2
— Single Engine Climb	94D
— Starting	28
Entrance — Emergency	44
Equipment — Description & Operation of Auxiliary Equipment	47-54
— Emergency Equipment Diagram	38
— Miscellaneous	53
— Radio & Navigation	73
— Relief	54
— Table (Communications)	49
Explanation of Weight Limitations Chart	60
Exterior Inspection	25
Exterior Lighting	53
Extinguishers & Controls — Fire	22

F

Failure — Engine	37
— Engine Failure Procedures	37-41
— Propeller	41
Feathering Buttons — Propellers	3
Feathering — Propeller	3
Filter Switches — Radio Range	51
Fire — Electrical Fire in Flight	42
— Engine Fire in Flight	42

— Engine Fire on the Ground	41
— Extinguisher Controls & Indicators	22
— Extinguisher (Engine)	22
— Extinguisher (Hand)	22
— Fuselage Fire in Flight	42
— Wing Fire in Flight	42
First Aid Kits	24
Flap Lever — Wing	18
Flaps — Cowl Flap Handles	2
— Position Indicator	18
— System Emergency	45
— Wing	18
Flight — Characteristics	61-62
— Checks (Pre-Flight)	25-30
(In-Flight)	31-35
(Post-Flight)	36
(Night-Additional)	28
— Cold Weather Operation	76-78
— Control System	16-18
— Desert Procedures	78
— Instrument Flight Operation	71-75
— Instrument Flight Radio & Navigation Equipment	73
— Report Case	54
— Turbulence & Thunderstorms	75
Fuel Booster Pump Switches	9
Fuel Flow Per Engine	92-94A
Fuel — Nautical Miles Per Engine	88-91
Fuel Pressure Drop Engine Operating	39
Fuel Quantity Data Chart	13
Fuel Selector Handles — Engine	8
Fuel System	6
— Booster Pumps (Operation)	63
— Diagram	12
— Emergencies	44
— Indicators	9
Fuel Tank Sequence	63

G

Gage — Carburetor Air Temperature	3
— Fuel System Indicators	9
— Instruments (Pitot & Static)	21-22
— Loadmeters	11
— Manifold Pressure	3
— Tab Position Indicators	17-18
— Tachometer	3
— Units (Engine)	3
— Vacuum Indicators	16
G. C. A. Letdown & Diagram	74
Gear — Landing Gear System,	
Controls & Indicators	18-20
— Landing Gear System Emergencies	45
— Limitations	60
Generators	10
— Inoperative Lights	11
— Loadmeters	11
— Switches	11
Glide — Maximum Glide Chart	46

Go Around	35
Go Around — Single Engine	41
Ground Fire	41

H

Hand Crank — Emergency Flap Operation	18
— Emergency Gear Operation	20
Hand Fire Extinguisher	22
Handles — Cowl Flap	1
— Emergency Cabin Door Release	24
— Emergency Escape Hatch Release	24
— Engine Fuel Selector	8
— Parking Brake	21
— Suction Cross Feed	9
Harness — Shoulder	24
Head Temperature Gage — Cylinder	3
Heat — Cabin Heat Buttons	47
— Carburetor Anti-icing	75
— Levers (Manifold)	1
— Pilot Compartment Outlet Shut-Off	47
— Pitot Heater, Switches & Operation	51
Heating & Ducting & Windshield Defrosting	47
High Weight Landing	35
Holding — Instrument Flight	73

1

Ice, Snow & Rain	74
Icing — Anti-icing & De-icing Equipment	
Controls & Operation	47-51
— Carburetor Anti-icing	75
— Pitot Anti-icing	51
— Propeller Anti-icing	48
— Windshield Defrosting	47
— Wing & Tail De-icer	75
— Wing & Tail De-icing	50
Ignition Booster Switch	3
Ignition Switches	2
Indicators — Aileron & Rudder	17
— Elevator	18
— Engine	3
— Engine	56-57
— Engine Fire Extinguisher	22
— Flap Position	18
— Flight Tab Position	17
— Fuel System	9
— Generator Inoperative Lights	11
— Instruments	21
— Landing Gear Position	20
— Marker Beacon Receiver	
R-122/ARN-12	51
— Radio Compass AN/ARN-7	51
— Vacuum System	16
In Flight — Cold Weather Operation	77
— Electrical Fire	42
— Engine Failure	39
— Engine Fire	42
— Fuselage Fire	42
— Operational Instruction Charts	82-93

— Propeller Failure	41
— Restarting Engine	39
— Turbulence & Thunderstorms	75
— Wing Fire	42
Inoperative Lights — Generators	11
Inspection — Before Exterior	25
— Before Leaving Aircraft	36
— Exterior	25
— Exterior Inspection Diagram	26
— Interior	27
— Night Flight (Additional)	28
Instructions — Taxiing	30
Instruments	21
— Engine	3
— Flap Position Indicators	18
— Fuel System	9
— Inverter	11
— Inverter Switch	13
— Landing Gear Position Indicators	20
— Lighting Control	53
— Markings	56
— Radio Compass AN/ARN-7	51
— Static & Pitot Pressure	22
Instrument Flight	71-74
— Approaches & Diagrams	73-74
— Climb	72
— Cruising Flight	73
— Descent	73
— Holding	73
— Radio & Navigation Equipment	73
— Take-Off	71
Interior Heating & Windshield Defrosting	47
Interior Lighting	52-53
Interphone RC-36	51
Interphone Selector Switch & Volume Control	51
Inverter — Instrument	11
Inverter — Instrument Inverter Switch	13

J

K

Kits — First Aid	24
Kits — Mooring	54

L

Landing — After Landing Checks	36
— Before Leaving Aircraft Checks	36
— Characteristics	61
— Cold Weather	77
— Cross Wind	34
— Curve	94E
— Emergencies (Deflated Tires, Unprepared Runways & Wheels Up)	43-44
— High Weight	35
— Minimum Run	35

— Night	33
— Normal	35
— Pattern	34
— Pattern (One Engine)	40
— Single Engine	40
— With No Power	41
Landing Gear — Controls & Operation	18-20
— Emergency Clutch	20
— Emergency Hand Crank	20
— Lever	19
— Lever Emergency Release	19
— Limitations	60
— Malfunction Light	19
— Position Indicators	20
— System Emergency	45
— Tail Wheel Lock System & Control	20
— Warning Horn & Silencer	20
Landing Lights — Limits	55
— Switch	53
Lavatory & Baggage Compartment Lights	52
Leaning — Manual Leaning	63
Letdowns — G. C. A. Letdown & Diagram	74
— Radio Range Letdown & Diagram	73-74
Levers — Cowl Flaps	2
— Landing Gear	19
— Manifold Heat	1
— Mixture	1
— Oil Cooler Shutters	4
— Propeller	3
— Shoulder Harness Locking	24
— Throttle	1
— Wing Flap	18
Liaison Radio Selector Switch	51
Lighting — Control (Instruments)	53
— Equipment	52
— Exterior	53
— Interior	52
— Pilot's Compartment	52
— Radio Control Panel	52
Lights — Generator Inoperative	11
— Landing Gear Malfunction	19
— Landing Lights Limits	55
— Lavatory & Baggage Compartment	52
Light Switches — Cabin Dome	52
— Landing Lights	53
— Map Reading	52
— Navigation Lights	53
— Passing Light	53
— Radio Controls Spotlight Rheostat Switch	53
— Taxi Lights	53
— Utility Light	52
Limitations — Electrical System	55
— Engine	55
— Landing Gear	60
— Landing Lights	55
— Performance	60
— Operating	55-60
— Operating Weight	55

— Weight & Balance	55
— Weight Limitations Chart	59
— Wing	58
Load Analysis Charts — Electrical	64
Load Distribution	58
Load Factors & Margin of Safety	58
Loadmeters	11
Lock — Flight Control	16
Locking Lever — Shoulder Harness	24
Long Range Prediction Graphs	94G-94K

M

Main Differences Table	2
Malfunction Light — Landing Gear	19
Maneuvers Prohibited	55
Manifold Heat Levers	1
Manifold Pressure Gage	3
Manual Leaning	63
Map Case	53
Map Reading Light & Switches	52
Margin of Safety & Load Factors	58
Marker Beacon Receiver	
R-122/ARN-12	51
Marker Beacon Receiver Indicator & Operation R-122/ARN-12	51
Markings — Instrument	56
Master Switch Bar	10
Maximum Endurance	94F
Maximum Glide Chart	46
Minimum Crew	55
Minimum Run Landing	35
Minimum Run Take-Off	32
Minimum Safe Single Engine Airspeed	37
Miscellaneous Equipment	53
Mixture — Carburetor Air Temperature Gage	3
Mixture Levers	1
Mooring Kit	54

N

Nautical Miles Per Pound of Fuel Graphs	88-91
Navigation Lights Switch	53
Navigation & Radio Equipment (Instrument Flight)	73
Night Flight Check — Additional	28
Night Landing	35
No Power Available Landing	41
Normal Flight	32-33
— Landing	33
— Procedures	25-36
— Take-Off	31

O

Oil Bypass Buttons	6
Oil Coolers	4
Oil Cooler Shutter Levers	4
Oil Dilution Switches	6
Oil System	3
One Engine Landing Pattern	40

Operating Data	79-93
Operating Limitations	55-60
Operating Weight	58
— Limitations	55
— Limitations Chart	59
Operation — All Weather	71-78
— Anti-icing & De-icing Equipment	74-75
— Cold Weather	76-78
Operation & Description of Emergency Equipment	47-54
Operation — Desert Procedures	78
— Electrical System	68
— Emergency Operations	37-45
— Engine Ground Operation	29
— Fuel System	63
— Instrument Flight	71-74
— Normal Operation	25-36
— Pitot Heat	51
— Propeller Anti-icing	48
— Radios	51-52
— Systems Operation	63-68
— Turbulence & Thunderstorms	75
Outlet Shut-Off — Pilots Compartment Air	47
Overvoltage Relay	11

P

Panel — Radio Control Lighting	52
Panels — Audio Switch	51
Parking Brake Handle	21
Parking — Cold Weather	78
Passing Light Switch	53
Passenger Seats	54
Pattern — Landing	34
— Landing (One Engine)	40
Penetration — Turbulent Air Chart	72
Performance Limitations	60
Pilots Compartment — Air Outlet Shutoff	47
— Lighting	52
Pitot Heater Switches & Operation	51
Pitot & Static Pressure Source	22
Position Indicators — Flap	18
— Flight Tab	17-18
— Landing Gear	20
Post Flight Check	36
Power Change	63
Power — Electrical Supply System	10
Power — No Power Landing	41
Power Schedules	83-87
Power Switch — Pilots Turn & Bank	11
Power System Emergency — Electrical	45
Prediction Long Range	94G-94K
Pressure — Control Pressure	61
Pressure Drop Engines Operating Normally — Fuel	39
Pressure — Manifold Pressure Gage	3
Pressure Source — Pitot & Static	22
Procedures — All Weather	71-78
— Bail Out	44
— Cold Weather	76-78

— Crash Landing	41	Selector Switch & Volume Control Interphone	51
— Desert	78	Servicing Diagram	23
— Ditching	44	Shoulder Harness Locking Levers	24
— Emergency	37-45	Shutter Levers — Oil Coolers	4
— Fire	41-42	Silencer — Warning Horn	20
— Instrument Flight	71-73	Single Engine — Climb Curve	94D
— Landing Emergencies	43-44	— Emergency Climb	94M
— Let Down	73-74	— Go Around	41
— Normal Operating	25-36	— Landing	40
— Single Engine	38	— Procedures	38
— Systems Emergencies	44-45	— Safe Minimum Airspeed	37
— Turbulence & Thunderstorms	75	Smoke Elimination	42
Prohibited Maneuvers	55	Snow, Ice & Rain	74
Propellers	3	Source — Pitot & Static Pressure	22
— Anti-icing, Control & Operation	48	Space — Capacity	58
— Failure	41	Spins	61
— Feathering	3	Spotlight Rheostat — Radio Controls Light	53
— Feathering Buttons	3	Stability	61
— Icing	74	Stall Chart	62
— Levers	3	Stalls	61
Pumps — Fuel Booster	63	Starter Switch	3
— Fuel Booster Switches	9	Starting — Cold Weather	76
		— Engines	28
		— Engine Selector Switch	2
		— System	2
		Static & Pitot Pressure Source	22
		Stopping Engines	36
		— Before Stopping Engines	36
		— Cold Weather	77
		Suction Cross Feed	68
		Suction Cross Feed Handle	9
		Sump Drainage — Fuel (Cold Weather)	78
		Supply — Electrical Power System	10
		Switches — Battery	11
		— Cabin Dome Lights	52
		— Engine Starting Selector	2
		— Filter (Range)	51
		— Fuel Booster Pump	9
		— Generator	11
		— Ignition	2
		— Ignition Booster	3
		— Instrument Inverter	13
		— Landing Lights	53
		— Lavatory & Baggage	
		— Compartment Lights	52
		— Map Reading Lights	52
		— Master Bar	10
		— Navigation Lights	53
		— Oil Dilution	6
		— Passing Light	53
		— Pilots Turn & Bank Power	11
		— Pitot Heater	51
		— Primer	3
		— Starter	3
		— Selector & Volume Control	
		— (Interphone)	51
		— Taxi Lights	53
		— Utility Lights	52
		— Voltmeter	11
		Switch Panels — Audio	51

Q

Quantity — Fuel Data Chart	13
----------------------------	----

R

Radar Letdown & Diagram — G. C. A.	74
Radio & Communications Equipment	51
Radio Compass & Operation AN/ARN-7	51
Radio Control Panel Lighting	52
Radio Controls Spotlight Rheostat Switch	53
Radio & Navigation Equipment	
(Instrument Flight)	73
Radio Operation	51
Radio Range Letdown	74
Radio Range Letdown Diagram	73
Rain, Ice & Snow	74
Reading Light Switches — Map	52
Receiver Indicators	51
Relay — Overvoltage	11
Release — Cabin Door Emergency Handle	24
— Emergency Escape Hatch Handle	24
— Landing Gear Lever Emergency	19
Relief Equipment	54
Restarting Engine in Flight	39
R-122/ARN-12 Marker Beacon	
Receiver, Indicators & Operation	51
Rudder & Aileron Indicators	17
Runways — Landing on Unprepared Runways	43

S

Safe Minimum Airspeed — Single Engine	37
Safety & Load Factors — Margin	58
Seats	24
Seats — Passenger	54
Selector Handles — Engine Fuel	8
Selector Switch — Engine Starting	2

Systems — Anti-icing & De-icing	48
— Brake	20
— Electrical Limits	55
— Electrical Power Supply	10
— Flight Control	16
— Fuel	6
— Fuel Indicators	9
— Interior Heating & Windshield Defrosting	47
— Landing Gear	18
— Oil	3
— Starting	2
— Tail Wheel Lock & Control	20
— Vacuum	16
— Ventilation	47
Systems Diagrams — Electrical	14
— Fuel	12
Systems Emergencies — Electrical Power	45
— Flap	45
— Fuel	44
— Landing Gear	45
Systems Operation	63-68
— Electrical	68
— Fuel	63

T

Tab — Flight Controls	16
Tab — Position Indicators	17
Table — Communications Equipment	49
— Main Differences	2
Tachometer	3
Tail Wheel Lock System & Control	20
Tail & Wing De-icer	75
Tail & Wing De-icers	50
Take-Off — After	32
— Before	30
— Chart	83
— Climb Over Obstruction	32
— Cold Weather	77
— Cross Wind	31
— Curve	94B
— Desert	78
— Engine Failure	39
— Instrument	71
— Minimum Run	32
— Night	32
— Normal	31
Tank Sequence — Fuel	63
Taxiing — Cold Weather	77
— Instructions	30
Taxi Lights Switch	53
Temperature Gages — Carburetor Air	3
— Cylinder Head	3

Tests — Engine Ground	29
Throttle Levers	1
Tires Deflated Landings	43
Traffic & Pre-Traffic Pattern Checks	33
Turbulence & Thunderstorms Flight	75
Turbulent Air Penetration Chart	72
Turn & Bank — Pilots Power Switch	11

U

Units — Engine Gage	3
Use of the Charts & Problem (Flight Operation Instructions)	80
Use of the Chart (Weight Limitations)	60
Utility Light Switches	52

V

Vacuum System, Control & Indicators	16
Vent & Heat Diagram	48
Ventilation System	47
Voltage — Overvoltage Relay	11
Voltmeter Switch	11
Volume Control — Interphone	51

W

Warning Horn — Landing Gear	20
— Silencer	20
Weather — All Weather Operation	71-78
— Cold Weather Operation	76-78
— Desert Operation	78
Weight & Balance Limitations	55
Weight — Distribution	58
— Gross	58
— Limitations	55
— Limitations Chart	59
— Operating	58
Wheels — Landing Gear System, Controls & Operation	18-20
Wheels — Landing With Deflated Tires	43
Wheels Up Landing	44
Wind — Crosswind Landing	34
— Take-Off	31
Windshield Defrosting System	47
Windshield Wipers	53
Wing Flaps & Lever	18
Wing Limitations	58
Wing & Tail De-icer	75
Wing & Tail De-icers	50
Wipers — Windshield	53

X - Y - Z